

Super Touring and Time Trial

Car Classification Form 2019 (v3.3)

What Class do you Want to Compete In? *	
O ST1/TT1 - 6.00:1	
O ST2/TT2 - 8.00:1	
O ST3/TT3 - 10.00:1	
ST4/TT4 - 12.00:1	
O ST5/TT5 - 14.00:1	
○ ST6/TT6 - 18.00:1	
Calculation of Adjusted Weight/Powe	r Patio (workshoot):
ST5-6/TT5-6	i natio (worksheet).
313-0/113-0	
Minimum Composition Weight with Driver (Ibe) *	Weight Footor (STE 6/TTE 6)
Minimum Competition Weight with Driver (lbs) *	Weight Factor (ST5-6/TT5-6)
Minimum Competition Weight with Driver (lbs) * 2452	-0.30
2452	-0.30 Calculated
2452 Average Chassis Dyno Horsepower (Avg HP) *	-0.30 Calculated Raw Weight/Horsepower Ratio
2452	-0.30 Calculated
Average Chassis Dyno Horsepower (Avg HP) *	-0.30 Calculated Raw Weight/Horsepower Ratio 17.90
Average Chassis Dyno Horsepower (Avg HP) * 137 Use only whole number	-0.30 Calculated Raw Weight/Horsepower Ratio 17.90
Average Chassis Dyno Horsepower (Avg HP) * 137 Use only whole number Adjusted Weight/Horsepower Ratio	-0.30 Calculated Raw Weight/Horsepower Ratio 17.90
Average Chassis Dyno Horsepower (Avg HP) * 137 Use only whole number Adjusted Weight/Horsepower Ratio 18	-0.30 Calculated Raw Weight/Horsepower Ratio 17.90
Average Chassis Dyno Horsepower (Avg HP) * 137 Use only whole number Adjusted Weight/Horsepower Ratio 18 Calculated	-0.30 Calculated Raw Weight/Horsepower Ratio 17.90

Tires (ST5-6/TT5-6) *
 Tires with a UTQG Treadwear rating 100 or greater +0.5
Not Applicable
Brakes (ST5-6/TT5-6) *
Non-OEM, modified or relocated brake calipers/bracketsor rotor diameter -0.2
Not Applicable
Suspension (ST5-6/TT5-6) *
Suspension design utilizing upper "A-arm" or "wishbone" type control arms (front or rear) -0.7
 Replace, modify, or remove control arms, camber arms/links, toe arms/links -0.5
 Add, replace, or modify a Watts link, Panhard Rod, or Torque Arm -0.5
 Non-OEM metallic and/or spherical design replacement suspension bushing modifications on control/camber/toe arms/links, panhard rods, watts links, and torque arms (includes replaced, modified, adjustable, or altered control arm ball joints) -0.2
 Non-OEM shocks/struts with an external reservoir (or piggyback) OR with shaft diameter 40mm or greater -0.7
 Increase in track width greater than four (4) inches -0.7
□ Not Applicable
Chassis (ST5-6/TT5-6) *
One or more cage bars that penetrate the front bulkhead/firewall -0.3
 Not Applicable
Posts (OTC/TTC) *
Body (ST6/TT6) *
□ BTM Aero (see 6.1.4) +0.4
 Modification of the OEM roof line/shape and/or windshield/frame removal (convertibles only) -0.4
 Modification of the floor pan for exhaust clearance only and/or the rocker panel for side exit
exhaust only -0.2
exhaust only -0.2 Single rear wing or spoiler -1.0
•
☐ Single rear wing or spoiler -1.0
Single rear wing or spoiler -1.0✓ Not Applicable
 Single rear wing or spoiler -1.0 ✓ Not Applicable Transmission (ST5-6/TT5-6) *
 Single rear wing or spoiler -1.0 ✓ Not Applicable Transmission (ST5-6/TT5-6) * ○ OEM street-legal model available paddle shift/DCT/SMG or sequential motorcycle gearbox -0.3 ○ Not Applicable
 Single rear wing or spoiler -1.0 ✓ Not Applicable Transmission (ST5-6/TT5-6) * ○ OEM street-legal model available paddle shift/DCT/SMG or sequential motorcycle gearbox -0.3 • Not Applicable Drivetrain (ST5-6/TT5-6) *
 Single rear wing or spoiler -1.0 ✓ Not Applicable Transmission (ST5-6/TT5-6) * ○ OEM street-legal model available paddle shift/DCT/SMG or sequential motorcycle gearbox -0.3 • Not Applicable Drivetrain (ST5-6/TT5-6) * ○ AWD -0.5
 Single rear wing or spoiler -1.0 ✓ Not Applicable Transmission (ST5-6/TT5-6) * ○ OEM street-legal model available paddle shift/DCT/SMG or sequential motorcycle gearbox -0.3 • Not Applicable Drivetrain (ST5-6/TT5-6) * ○ AWD -0.5 • FWD +0.6
 Single rear wing or spoiler -1.0 ✓ Not Applicable Transmission (ST5-6/TT5-6) * ○ OEM street-legal model available paddle shift/DCT/SMG or sequential motorcycle gearbox -0.3 ○ Not Applicable Drivetrain (ST5-6/TT5-6) * ○ AWD -0.5 ○ FWD +0.6 ○ Rear-Mid or Rear engine layout (not Front-Mid) -0.4
 Single rear wing or spoiler -1.0 ✓ Not Applicable Transmission (ST5-6/TT5-6) * ○ OEM street-legal model available paddle shift/DCT/SMG or sequential motorcycle gearbox -0.3 • Not Applicable Drivetrain (ST5-6/TT5-6) * ○ AWD -0.5 • FWD +0.6